

CLAIM LISTING

1. (Original) A method for maintaining SIP contact addresses:
sending, by a SIP proxy user agent (UA), a first registration message for a remote unit to a SIP registrar;
sending a second registration message for the remote unit to the SIP registrar;
receiving, in response to the second registration message, a response that indicates a contact address more recent than any provided by the SIP proxy UA; and
sending, in response to the received response, a deregistration message for the remote unit to the SIP registrar.
2. (Original) The method of claim 1 further comprising receiving, by the SIP proxy UA, a non-SIP registration request from the remote unit prior to sending the first registration message.
3. (Original) The method of claim 1 wherein the second registration message is sent in response to a registration timer expiration.
4. (Original) The method of claim 1 wherein the first registration message comprises a SIP REGISTER message.
5. (Original) The method of claim 4 wherein the SIP REGISTER message indicates that it comprises a new contact address.
6. (Original) The method of claim 1 wherein the second registration message comprises a SIP REGISTER message.

BEST AVAILABLE COPY

7. (Original) The method of claim 1 wherein the response that indicates a contact address more recent than any provided by the SIP proxy UA comprises a SIP 200 OK message and at least one creation time stamp.
8. (Original) The method of claim 7 wherein the response further comprises a group of contact addresses and a creation time stamp for each.
9. (Original) The method of claim 1 wherein the deregistration message comprises a SIP REGISTER message with an Expires header value of "0".

BEST AVAILABLE COPY

10. (Original) A method for maintaining SIP contact addresses:

receiving a first registration message for a remote unit from a first SIP proxy user agent (UA);

storing, as a member of a group of contact addresses for the remote unit, both a first contact address based on the first registration message and a first creation timestamp for the first contact address;

receiving a second registration message for the remote unit from a second SIP proxy UA after receiving the first registration message;

storing, as a member of the group of contact addresses for the remote unit, both a second contact address for the remote unit and a second creation timestamp for the second contact address;

receiving a third registration message for the remote unit from the first SIP proxy UA;

sending, in response to the third registration message, a response that indicates a contact address more recent than any provided by the first SIP proxy UA;

receiving a deregistration message for the remote unit from the first SIP proxy UA; and

removing, from the group of contact addresses for the remote unit, the first contact address.

11. (Original) The method of claim 10 wherein the response that indicates a contact address more recent than any provided by the first SIP proxy UA comprises a SIP 200 OK message and at least one creation time stamp.

12. (Original) The method of claim 11 wherein the response further comprises a group of contact addresses and a creation time stamp for each.

BEST AVAILABLE COPY

13. (Original) The method of claim 10 wherein the first registration message comprises a SIP REGISTER message, the second registration message comprises a SIP REGISTER message, and the third registration message comprises a SIP REGISTER message.

14. (Original) The method of claim 10 wherein the deregistration message comprises a SIP REGISTER message with an Expires header value of "0".

BEST AVAILABLE COPY

15. (Original) A radio access network (RAN) component comprising:
- a wireless network interface; and
 - a SIP proxy user agent, communicatively coupled to the wireless network interface, adapted to
 - receive a registration request from a remote unit via the wireless network interface,
 - send a first registration message for the remote unit to a SIP registrar,
 - send a second registration message for the remote unit to the SIP registrar,
 - receive, in response to the second registration message, a response that indicates a contact address more recent than any provided by the SIP proxy UA, and
 - send, in response to the received response, a deregistration message for the remote unit to the SIP registrar.

BEST AVAILABLE COPY

16. (Original) A SIP registrar comprising:
a SIP location data base; and
a SIP location processor, communicatively coupled to the SIP registration data base, adapted to
receive a first registration message for a remote unit from a first SIP proxy user agent (UA),
store in the SIP location data base, as a member of a group of contact addresses for the remote unit, both a first contact address based on the first registration message and a first creation timestamp for the first contact address,
receiving a second registration message for the remote unit from a second SIP proxy UA after receiving the first registration message,
storing in the SIP location data base, as a member of the group of contact addresses for the remote unit, both a second contact address for the remote unit and a second creation timestamp for the second contact address,
receiving a third registration message for the remote unit from the first SIP proxy UA,
sending, in response to the third registration message, a response that indicates a contact address more recent than any provided by the first SIP proxy UA,
receiving a deregistration message for the remote unit from the first SIP proxy UA, and
removing, from the group of contact addresses for the remote unit, the first contact address.

BEST AVAILABLE COPY